

digital fast input 1801



- 8 bit digital fast input 200 µsec
- Galvanically isolated
- Shock and vibration approved
- Single wire
- 24 VDC inputs
high >+16 V, low <+6 V

TRsystems GmbH, Eglisshalde 16, 78647 Trossingen, Tel.: +49 (0) 7425 228-0, Fax: +49 (0) 7425 228-34, www.trsystems.de, info@trsystems.de




Pinout

LED	Signal
0; (8)	I 00 input active >+16 V
1; (9)	I 01 input active >+16 V
2; (10)	I 02 input active >+16 V
3; (11)	I 03 input active >+16 V
4; (12)	I 04 input active >+16 V
5; (13)	I 05 input active >+16 V
6; (14)	I 06 input active >+16 V
7; (15)	I 07 input active >+16 V

LED	Signal
E:	-
P:	Power supply active, red
PIN	Signal
1	I 00 Input 0
2	I 01 Input 1
3	I 02 Input 2
4	I 03 Input 3
5	I 04 Input 4
6	I 05 Input 5
7	I 06 Input 6
8	I 07 Input 7
9	Power +24 V
10	Power 0 V
11	Power +24 V
12	Power 0 V
13	Power +24 V
14	Power 0 V

All Power +24 V and All 0 V are internal connected



Attributes

Dataformat:
Standard byte (8 bit) format

- Applications:**
8 bit digital fast input
Available prints:
- @P1801L: 8 bit, 24 VDC, 200 µsec
 - @P1801R: 8 bit, 24 VDC, 200 µsec

- Related Applications:**
- 8 bit digital input:
 - @P1800: 8 bit, 24 VDC, 2 msec
 - 8 bit digital input; +12 V
 - @P1803: 8 bit, 12 VDC, 2 msec
 - 4 bit digital input; 3-wire:
 - @P1400: 4 bit, 24 VDC, 2 msec
 - 8 bit digital input with 10k Ohm
 - @P1804: 8 bit, 24 VDC
10k Ohm Pull Down

Electrical Data

Power supply external.....	0 V required (+24 V ±20 % optional, not required for input function)
Operating current	0 mA at +24 V
Operating current @ctiveBus	85 mA at +3,3 V / 0 mA at +5 V
Input protection	+30 V overvoltage, surge
Input resistance.....	15 KΩ
Input current.....	≤ 2 mA at +24 V
Input filter	200 µsec

digital fast input 1801

System Information

System ID	0x0006
System address space	8 bit in, 8 bit out

Environmental Conditions


Electromagnetic compatibility (EMC)	EN61000-6-4 according EN55011
.....	EN61000-6-2 according EN61000-4-2, -4-4
Operating temperature [°C]	0 .. +55
Storage temperature [°C]	-20 .. +70
Humidity (rel.)	98 % (non condensing)
Protection class*	IP 20 (DIN 40 050)

*The protection class is valid only with housing and connector installed

Mechanical Data PCB

Weight	approx. 0.05 kg including connector
Dimension	105 mm x 80 mm x 12 mm

Drawing (effective if mounted in @M housing)



Ordering Key

